

iSpeaker DCS60

60W Dante Column Speaker





INTRODUCTION

The iSpeaker DAS60 is designed to be used in speaking sound amplification applications such as video conference rooms, digital courts, conference centers, lecture halls, lecture theaters, etc., as well as background music applications in various architectural spaces such as churches, museums, transportation hubs, and square public areas.

Solve the problem that traditional conference room speakers are too big and unsightly when hung on the wall.

FEATURES

- 4x2.5" Neodymium Magnets
- Sensitivity of 93dB
- Rated power 60W
- Supports Dante
- Supports PoE: 802.3af/802.3at/802.3bt
- Diffusion angle: 20° vertically, 120° horizontally
- Streamlined design and a newly designed industrial black color.
- It is suitable for sound reinforcement in various architectural spaces and has beautiful sound quality.
- ABS mixed aluminum alloy reinforced cabinet, strong and durable.
- The newly designed circular waveguide hole forms a unique low-frequency heart-shaped diffusion, the treble is crisp and pleasant, the sound performance is natural and thick, and with full bass.

TECHICAL SPEC

Model	iSpeaker DCS60
Name	60W Dante Column Speaker
Structure	4x 2.5" Neodymium Magnets
Rated impedance	4Ω
Rated power	60W
Effective frequency range	106Hz~20KHz
Sensitivity level (1m/1W)	93dB
Diffusion angle	20° vertically, 120° horizontally
Sound pressure level	In specified frequency band: 109dB
Cover material	Metal mesh
Chassis material	ABS mixed aluminum alloy reinforced cabinet
Installation dimension	Adjustable angels wall-mounting
Port	Dante RJ45 PoE
PoE	802.3af/802.3at/802.3bt
Color	Black (Default); Apple Gray (Customized)
Net Weight	6.3kg
Gross Weight	8.3kg
Dimension	670x100x80mm

